

Main

Range of product	Actassi
Product or component type	Fibre optic cable multi mode



Complementary

Fibre performance	OM2+ (50/125 µm)
Optic fibre type	Tight buffered, Ø = 900 µm (indoor)
Condition of use	Indoor
Attenuation	<= 3.5 dB / 1 km at 850 nm <= 1.5 dB / 1 km at 1300 nm
Cable weight	20 kg / 1 km
Bending radius	10.2 cm (loaded) 5.1 cm (installed)
Numerical aperture	0.2 (+/- 0.015)
Number of optic fibre	6
Standard	LSZH (low smoke zero halogen)

Environment

Ambient air temperature for operation	-20...75 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Strength (aramid yarn)

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2016
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.